

ON 長效 OAT 水箱精

產品規格

Part No.: ON-CL0001

Description:

本產品為乙二醇基長效冷卻液，採用複合型 OAT 長效防蝕技術，能穩定提供抗腐蝕、抗沸騰、抗凍結與抗結垢保護，並有助於保護冷卻系統中的金屬、塑膠、橡膠密封件及管路。

Suitable For Use:

AS 2108-2004、AS/NZS 2108-2004 Type A、ASTM D-3306、ASTM D-4985、BS 6580:2010、China National GB 29743-2013、CUNA NC 956-16、TL 774-L、ONORM V 5123、PN-C40007:2000、SAE J1034、SANS 1251:2005、Toyota Long Life TSK 2601G。

Typical Inspections:

Physical	Unit	Specifications	Typical	Test Method
Color	-	-	Visual	-
Total Glycol by Weight(undiluted)	%	95~99	97	-
Total Glycol by Weight(60% water)	%	39~41	40	-
Total Glycol by Weight(50% water)	%	49~51	50	-
Total Glycol by Weight(40% water)	%	59~61	60	-
Total Glycol by Weight(30% water)	%	69~71	70	-
pH (undiluted)	-	7.0~9.0	8.38	ASTM D 1287
Boiling Point (undiluted)	°C	-	173	ASTM D 1120
Boiling Point (60% water)	°C	-	105.6	ASTM D 1120
Boiling Point (50% water)	°C	-	107.2	ASTM D 1120
Boiling Point (40% water)	°C	-	110.1	ASTM D 1120
Boiling Point (30% water)	°C	-	116.7	ASTM D 1120
Room Temperature Foam	ml	-	1	ASTM D 4921
40% concentrate - 60% water	°C	-	-21	ASTM D 1177
50% concentrate - 50% water	°C	-	-33	ASTM D 1177
60% concentrate - 40% water	°C	-	-45	ASTM D 1177
70% concentrate - 30% water	°C	-	-64	ASTM D 1177

Pack Sizes:

ON-CL0001(綠) / 1L x12	ON-CL0001B(綠) / 20L	ON-CL0006B(綠) / 20L (50% WATER)
ON-CL0002(紅) / 1L x12	ON-CL0002B(紅) / 20L	ON-CL0007B(紅) / 20L (50% WATER)
ON-CL0003(藍) / 1L x12	ON-CL0003B(藍) / 20L	ON-CL0008B(藍) / 20L (50% WATER)
ON-CL0004(紫) / 1L x12	ON-CL0004B(紫) / 20L	ON-CL0009B(紫) / 20L (50% WATER)
ON-CL0005(粉) / 1L x12	ON-CL0005B(粉) / 20L	ON-CL0010B(粉) / 20L (50% WATER)

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

www.onauto.co