

HD-C 重型柴油合成機油 10W-40 CK-4

產品規格

Part No. : ON-CV0001B

Description :

高品質重型柴油引擎機油，符合 API CK-4 與 ACEA E8/E11 等商用車用油規範，具優異的抗氧化穩定性、抗磨耗保護與低溫啟動流動性。適用於高負荷柴油引擎及配備後處理系統之商用車輛，可維持引擎清潔、降低磨耗並提供長效穩定潤滑表現。

Type Of Use :

API CK-4/SN	ACEA E8/E11	JASO DH-2
MB 228.51	MAN 3477、CES 20086	Renault RLD-4
MACK EOS-4.5	Volvo VDS 4.5	Detroit Diesel DDC93K222
Scania LDF-3		

Typical Inspections :

Physical	Unit	Specifications	Typical	Test Method
Color	-	L2.5~3.5	L3.0	ASTM D-1500
Density at 20 deg C	kg/L	Report	-	ASTM D-4052
Viscosity at 40 deg C	cSt	-	107.6	ASTM D-445
Viscosity at 100 deg C	cSt	12.5~16.3	15.5	ASTM D-445
Viscosity Index	-	MIN.140	153	ASTM D-2270
Total Base Number	mg KOH/g	MIN.9.0	9.8	ASTM D-2896
Cold-Cranking Simulator	cP	MAX.7,000	5,969	ASTM D-5293
Flash Point COC	°C	MIN.200	248	ASTM D-92
Pour Point	°C	-	-35	ASTM D-97

Pack Sizes :

ON-CV0001B / 20L
ON-CV0001D / 200L