

ON 齒輪油 75W90 GL-5 LSD

產品規格

Part No. : ON-GR0003B

Description :

用於齒輪及限滑差速器潤滑，適合要求 GL-5 75W-90 並具限滑需求的系統。

Type Of Use :

API GL-5	API MT-1	Meritor 076-A 076-D	
Ford WSP-M2C197-A	Scania ST0 1:0	Mack G0-J	SAE J2360
AIST 224	AGMA 9005-E02	Cincinnati Machine	DIN 51517:3
Limited Slip	VW G055 145 A2	VW G 052 145 S2	

Typical Inspections :

Property	Unit	Specifications	Typical	Test Method
Color	-	1.5~2.5	2.0	ASTM D 1500
Viscosity at 40 deg °C	cSt	-	101.78	ASTM D 445
Viscosity at 100 deg °C	cSt	14.0~24.0	14.83	ASTM D 445
Viscosity Index	-	>140	152	ASTM D 2270
Flash Point, COC	°C	>200	224	ASTM D 92
Pour Point	°C	-	-33	ASTM D 97

Pack Sizes :

ON-GR0003B / 20L

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

<https://www.onauto.com.tw/>