

ON AF46 無鋅高性能抗磨液壓油

產品規格

Part No. : ON-HY0001B

Description :

採無鋅、無灰配方，用於液壓系統潤滑，協助減少運轉時的磨耗，適合指定使用 46 號液壓油的設備。

Type Of Use :

Denison Parker HF-0, HF-1, HF-2 Eaton 35VQ25
Cincinnati Machine P68, P69, P70 DIN 51524 part II ISO 11158 ASTM D6158
SAE MS 1004 Bosch Rexroth RE 90220 GM LS-2
Conestoga pump test ISO 20763

Typical Inspections :

Property	Unit	Specifications	Typical	Test Method
Color	-	0.5~1.5	1.0	ASTM D 1500
Viscosity at 40 deg °C	cSt	41.4~50.6	46.74	ASTM D 445
Viscosity at 100 deg °C	cSt	-	6.88	ASTM D 445
Viscosity Index	-	>90	102	ASTM D 2270
Total Acid Number	mg KOH/g	>0.1	0.22	ASTM D 2896
Flash Point, COC	°C	>200	242	ASTM D 92
Pour Point	°C	-	-30	ASTM D 97

Pack Sizes :

ON-HY0001B / 20L

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

<https://www.onauto.com.tw/>