

ON AWS 高效抗磨液壓油 7000 PSI

產品規格

Part No. : ON-HY0003B

Description :

本產品提供ISO VG 32、46及68三種黏度規格，具良好的潤滑保護、黏度穩定性及低溫流動性能，適用於一般工業設備、工具機與移動式液壓系統。可依設備製造商指定黏度、工作溫度及操作條件選用。

Type Of Use :

Parker Denison HF-0, HF-1, HF-2	Bosch Rexroth RDE 90235
DIN 51524 Part 2(HLP)	ISO 6743-4 ISO-L-HM
ASTM D6158 HM	ISO 11158 HM
AFNOR NF E 48-603	SS 155434
VDMA 24318	SEB 181 222
Eaton E-FDGN-TB002-E	U.S. Steel 127, 136
Cincinnati Machine P-68, P-69, P-70	Vickers M-2950-S, I-286-S

Typical Inspections :

Property	Unit	Test Method	ISO VG 32	ISO VG 46	ISO VG 68
Color	-	ASTM D1500	0.5	0.5	0.5
Kinematic Viscosity at 40 °C	cSt	ASTM D445	32.12	46.43	68.77
Kinematic Viscosity at 100 °C	cSt	ASTM D445	5.47	6.83	8.84
Viscosity Index	-	ASTM D2270	103	101	101
Total Acid Number	mg KOH/g	ASTM D974	0.85	0.85	0.85
Flash Point, COC	°C	ASTM D92	236	242	248
Pour Point	°C	ASTM D97	-30	-30	-27

Pack Sizes :

ON-HY0003B / 20L (AWS 68)
ON-HY0004B / 20L (AWS 46)
ON-HY0005B / 20L (AWS 32)

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

<https://www.onauto.com.tw/>