

ON Hybrid 汽車全合成機油 0W-20

產品規格

Part No. : ON-PV0001

Description :

用於建議使用低黏度機油之油電車、新世代汽油引擎與節能車款。全合成配方有助於降低冷啟動阻力，提供良好潤滑保護、引擎清淨性與燃油經濟性，適合日常通勤與頻繁啟停行駛環境。

Type Of Use :

API SQ/RC、ACEA A5/B5、ILSAC GF-7A、GM dexos 1 Gen 3、Fiat Chrysler MS-6395、GM 6094M WSS-M2C947-A、WSS-M2C947-B1、WSS-M2C962-A1

Typical Inspections :

Physical	Unit	Specifications	Typical	Test Method
Appearance	-	Brown	-	-
Color		2.0~3.0	2.5	ASTM D 1500
Viscosity at 40 deg C	cSt	-	45.61	ASTM D 445
Viscosity at 100 deg C	cSt	6.9~9.3	8.86	ASTM D 445
Viscosity Index	-	160	168	ASTM D 2270
Total Base Number	mg KOH/g	7.0	8.4	ASTM D 2896
Cold-Cranking Simulator	cP	7000	6021	ASTM D 5293
Flash Point COC	deg C	200	210	ASTM D92
Pour Point	deg C	-	-35	ASTM D97

Pack Sizes :

ON-PV0001 / 12x1L

ON-PV0001B / 20L

ON-PV0001C / 60L

ON-PV0001D / 200L

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

www.onauto.co