

ON Advanced 汽車全合成機油 5W-30

產品規格

Part No. : ON-PV0002

Description :

用於新世代汽油引擎與一般乘用車保養需求。全合成配方有助於維持引擎清淨、抗磨耗保護與高溫油膜穩定性，適合日常行駛、長途行車及多元用車環境。

Suitable For Use :

API SQ、ACEA A5/B5、ILSAC GF-7、GM dexos 1 Gen 3、GM 4718M、GM 6094M、HONDA/ACURA HTO-06、WSS-M2C929-A、WSS-M2C946-A、WSS-M2C946-B1、WSS-M2C961-A1

Typical Inspections :

Physical	Unit	Specifications	Typical	Test Method
Color		2.5~3.5	2.5	ASTM D 1500
Viscosity at 40 deg C	cSt	-	66.98	ASTM D 445
Viscosity at 100 deg C	cSt	9.3~12.5	11.36	ASTM D 445
Viscosity Index	-	160	164	ASTM D 2270
Total Base Number	mg KOH/g	7.0	7.58	ASTM D 974
Flash Point COC	deg C	200	240	ASTM D92
Pour Point	deg C	-	-35	ASTM D97

Pack Sizes :

ON-PV0002 / 12x1L

ON-PV0002B / 20L

ON-PV0002C / 60L

ON-PV0002D / 200L

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

www.onauto.co