

SC-S 速克達合成機油 15W-40

產品規格

Part No. : ON-SCS1540

Description:

專為街道騎乘的速克達車款所設計的高品質合成機油，具出色的降低運轉噪音、減震與抗磨效果，在各種騎乘條件下，都能提供優異的引擎保護性能與潤滑。僅適用於空/水冷四行程引擎的乾式離合器車款。

Meet the Requirement:

JASO MB

Recommendations:

API SL

Typical properties:

Physical	Unit	Specifications	Typical	Test Method
Color	-	L2.0~3.0	L2.5	ASTM D-1500
Viscosity at 40 deg C	cSt		121.83	ASTM D-445
Viscosity at 100 deg C	cSt	12.5~16.3	15.58	ASTM D-445
Viscosity Index	-	MIN.130	135	ASTM D-2270
Total Base Number	mg KOH/g	MIN.7.0	7.48	ASTM D-2896
Flash Point COC	°C	MIN.200	246	ASTM D-92
Pour Point	°C		-27	ASTM D-97
Phosphorus	%wt	MIN.0.08	0.08	ASTM D 5185
Foming Tend/Stab	mL/mL			ASTM D 892
Sequence I at 24°C		MAX.10/0	5/0	ASTM D 892
Sequence II at 93.5°C		MAX.50/0	10/0	ASTM D 892
Sequence III at 24°C after 93.5°C		MAX.10/0	5/0	ASTM D 892

Pack Sizes:

ON-SCS1540A / 800ml x12

ON-SCS1540 / 1L x12

ON-SCS1540B / 20L

ON-SCS1540C / 60L