

ON CVT FWLV 變速箱油 紅色

產品規格

Part No. : ON-TF0003

Description :

本產品是一款先進的低黏度CVT 專用油，旨在提升現代節能車型與混合動力車型的燃油經濟性，並提供卓越的極壓保護與低溫性能。

Suitable For Use :

Chery WCF-1/Shell SL 2100、Daihatsu AMMIX CVTF DFE、GM/Saturn DEX-CVT、GM VT40 /GM HP CVT、Honda HCF2、Lexus Fluid FE、Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)、Mitsubishi CVTF ECO J4、Nissan NS-3、Opel/Vauxhall 7-speed CVT, 95529854、Perodua D-CVT、Subaru Lineartronic chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711、Subaru Lineartronic chain CVT 3 Fluid、Subaru Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700、Subaru High Torque CVTF-LV、Suzuki CVTF 4401、Suzuki CVT Green 2、Toyota CVTF FE、VW/Audi TL 521 16 (G 052 516)、VW/Audi TL 521 80 (G 052 180 A2)、Honda e:HEV、Honda iMMD、Honda Ultra HEVF-Type 1、Jatco CVT 8 Hybrid、Mazda SKYACTIVE-HYBRID、Nissan Altima Hybrid。

Typical Inspections :

Physical	Unit	Specifications	Typical	Test Method
Density at 20 deg C	kg/l	-	Report	ASTM D 4052
Viscosity at 40 deg C	cSt	-	33.45	ASTM D 445
Viscosity at 100 deg C	cSt	5.0	6.5	ASTM D 445
Viscosity Index	-	130	156	ASTM D 2270
Flash Point COC	deg C	180	208	ASTM D92
Pour Point	deg C	-	-48	ASTM D97

Pack Sizes :

ON-TF0003 / 1L

ON-TF0003B / 20L

Boschman Enterprise Co., Ltd

No. 36, Wuquan Rd., Wugu Dist., New Taipei City, Taiwan

www.onauto.co